TC6 Hand Held Temperature Sensor Probe

Τ4

TC6	Hand Held Thermocouple
T1	Model Type
C1	1 to 5 foot TPE retractable cord ³
C2	2 to 10 foot TPE retractable cord ³
	•
T2	Connector Type
SC	Standard connector
MC	Miniature connector
	•
Т3	Thermocouple Type
κ	Type K (yellow/ red)
J	Type J (white/ red)
Т	Type T (blue/ red)
E	Type E (purple/ red)
RTD	100Ω Pt. 385 Class A, 3-wire

TC6

T1

T2

_

Т3

Т4	Sensor Probe "L" Length (inches)

T6


"inches" Specify length in inches

Τ5

T5	Sensor Probe Diameter
16	0.063" (1/16 inch) ⁴
18	0.125" (1/8 inch) ⁴
36	0.188" (3/16 inch)
14	0.250" (1/4 inch)

Т6	Sensor Tip Construction
R	Round
Ρ	Pointed
E	Exposed ⁴

Outline & Dimensions



NOTES:

- 1. Part number example: TC6-C1-MC-K-12-14-R
- 2. Black multi-wall heat shrink covers sensor transition, 5" overall typically 1" on sensor probe and 2" on retractable cord
- 3. TPE is a thermoplastic elastomer that is acceptable for indoor and outdoor use up to 104°C
- 4. Option available for thermocouple probes only
- 5. Bold text indicates most common part selections



Section: Thermocouple Sensor Probes & Assemblies File: Handheld-Thermocouple-Sensor-Probe-TC6-1

Aircom Instrumentation Ltd. 9328 - 37 Avenue NW Edmonton, AB T6E 5K3 Ph: (780) 434-6916 Sales@AircomInstrumentation.com www.AircomInstrumentation.com